

CERTIFICATE

Issued to:
Applicant:
HEP Tech Co., Ltd.
No. 20, Jingke 7th Rd., Nantun Dist.,
40852 Taichung City, Taiwan

Licensee:
HEP GmbH
Ramsloh 10
58579 Schalksmühle, Germany

Product : Current controlled independent LED Driver
Trade name(s) : HEP GROUP®
Type(s)/model(s) : LSC3W200LR-Z UNI, LSC3W350LR-Z UNI, LSC3W500LR-Z UNI and
LSC3W700LR-Z UNI

The product and any acceptable variation thereto as specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to EN 61347-1:2015, EN 61347-1:2015/A1:2021, EN 61347-2-13:2014, EN 61347-2-13:2014/A1:2017 and EN IEC 62384:2020
- an inspection of the factory location according to CENELEC Operational Document CIG 021
- a DEKRA certification agreement with the number 2013493


DEKRA hereby grants the right to use the ENEC certification mark.

The ENEC certification mark may be applied to the product as specified in this certificate for the duration and under the conditions of the ENEC certification agreement.

This certificate is issued on 4 December 2023 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 88-133172

DEKRA Certification B.V.



B.T.M. Holtus
Managing Director



K. Lin
Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE
DUTCH ACCREDITATION
COUNCIL



SPECIFICATION OF THE CERTIFIED PRODUCT**Product data**

| | |
|--------------------------------|--|
| Product | : Current controlled independent LED Driver |
| Trade name(s) | : HEP GROUP® |
| Type(s)/model(s) | : LSC3W200LR-Z UNI, LSC3W350LR-Z UNI, LSC3W500LR-Z UNI and LSC3W700LR-Z UNI |
| Rated supply voltage | : 100-240 Vac |
| Supply frequency | : 50-60 Hz |
| Ambient temperature range (ta) | : -20...+50°C |
| Max. case temperature (tc) | : 70 °C |
| Degree of protection | : IP20 |
| Protection class | : II |
| Classification of installation | : independent |

Product data – type LSC3W200LR-Z UNI

| | |
|----------------------|-------------|
| Rated supply current | : 85 mA |
| Power factor | : 0,5–0,65C |
| Rated output voltage | : 13-18 Vdc |
| Rated output current | : 200 mA |
| Rated output power | : 2,6-3,6 W |
| Uout | : 28 V |

Product data – type LSC3W350LR-Z UNI

| | |
|----------------------|--------------|
| Rated supply current | : 85 mA |
| Power factor | : 0,4–0,65C |
| Rated output voltage | : 2,7-10 Vdc |
| Rated output current | : 350 mA |
| Rated output power | : 1-3,5 W |
| Uout | : 17 V |

Product data – type LSC3W500LR-Z UNI

| | |
|----------------------|--------------|
| Rated supply current | : 85 mA |
| Power factor | : 0,45–0,65C |
| Rated output voltage | : 2,7-7 Vdc |
| Rated output current | : 500 mA |
| Rated output power | : 1,4-3,5 W |
| Uout | : 15 V |

Product data – type LSC3W700LR-Z UNI

| | |
|----------------------|-------------|
| Rated supply current | : 75 mA |
| Power factor | : 0,4–0,6C |
| Rated output voltage | : 2,7-4 Vdc |
| Rated output current | : 700 mA |
| Rated output power | : 1,9-2,8 W |
| Uout | : 15 V |

TESTS**Test requirements**

EN 61347-1:2015
EN 61347-1:2015/A1:2021
EN 61347-2-13:2014

EN 61347-2-13:2014/A1:2017
EN IEC 62384:2020

Test result

The test results are laid down in DEKRA test file 343159100.

Additional information

The LED controlgear is an independent SELV controlgear for LEDs with constant current. The insulation between primary and secondary is SELV and between primary and housing is considered as double insulation. The controlgear has screw terminals. The max. enclosure temperature under abnormal or fault conditions is 110°C.

The list of components is laid down in test report 3431591.50.

Conclusion

The examination proved that all requirements were met.

Factory locations

HEP GmbH
Ramsloh 10
58579 Schalksmühle, Germany

Weisen Electronic Co. Ltd.
No. 3 Yangchun Rd., Jinwan Dist.
519040 Zhuhai City Guangdong, China